

Package: RcppJagger (via r-universe)

September 11, 2024

Title An R Wrapper for Jagger

Version 0.0.2

Description A wrapper for Jagger, a morphological analyzer proposed in Yoshinaga (2023) <[arXiv:2305.19045](https://arxiv.org/abs/2305.19045)>. Jagger uses patterns derived from morphological dictionaries and training data sets and applies them from the beginning of the input. This simultaneous and deterministic process enables it to effectively perform tokenization, POS tagging, and lemmatization.

License GPL-2

Depends R (>= 4.0)

Encoding UTF-8

SystemRequirements C++17

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

URL <https://shusei-e.github.io/RcppJagger/>,
<https://www.tkl.iis.u-tokyo.ac.jp/~ynaga/jagger/index.en.html>

BugReports <https://github.com/Shusei-E/RcppJagger/issues>

LinkingTo Rcpp

Imports cli (>= 3.6.1), purrr (>= 1.0.0), Rcpp (>= 1.0.7), rlang (>= 1.1.0)

Suggests dplyr (>= 1.1.0), testthat (>= 3.1.5), tibble

Config/testthat.edition 3

LazyData TRUE

Repository <https://shusei-e.r-universe.dev>

RemoteUrl <https://github.com/shusei-e/rcppjagger>

RemoteRef HEAD

RemoteSha b5fd958cfb730267bc00cdf49806212f77d6c2f8

Contents

lemmatize	2
lemmatize_tbl	3
pos	3
pos_simple	4
sentence_example	5
tokenize	5
tokenize_tbl	6

Index

7

lemmatize

An R wrapper for Jagger's lemmatizer

Description

An R wrapper for Jagger's lemmatizer

Usage

```
lemmatize(input, model_path = NULL, keep = NULL, concat = TRUE)
```

Arguments

input	an input.
model_path	a path to the model.
keep	a vector of POS(s) to keep. Default is NULL.
concat	logical. If TRUE, the function returns a concatenated string. Default is TRUE.

Value

a vector (if concat = TRUE) or a list (if concat = FALSE).

Examples

```
data(sentence_example)
res_lemmatize <- lemmatize(sentence_example$text)
```

lemmatize_tbl	<i>An R wrapper for Jagger's lemmatizer (a tibble input)</i>
---------------	--

Description

An R wrapper for Jagger's lemmatizer (a tibble input)

Usage

```
lemmatize_tbl(tbl, column, model_path = NULL, keep = NULL)
```

Arguments

tbl	a tibble object.
column	a column name of the tibble to tokenize.
model_path	a path to the model.
keep	a vector of POS(s) to keep. Default is NULL.

Value

a tibble.

Examples

```
data(sentence_example)
res_lemmatize <- lemmatize_tbl(tibble::as_tibble(sentence_example), "text")
```

pos	<i>An R wrapper for Jagger's POS tagger</i>
-----	---

Description

An R wrapper for Jagger's POS tagger

Usage

```
pos(input, model_path = NULL, keep = NULL, format = c("list", "data.frame"))
```

Arguments

input	an input.
model_path	a path to the model.
keep	a vector of POS(s) to keep. Default is NULL.
format	a format of the output. Default is list.

Value

a list object.

Examples

```
data(sentence_example)
res_pos <- pos(sentence_example$text)
```

pos_simple

An R wrapper for Jagger's POS tagger (only returning POS)

Description

An R wrapper for Jagger's POS tagger (only returning POS)

Usage

```
pos_simple(
  input,
  model_path = NULL,
  keep = NULL,
  format = c("list", "data.frame")
)
```

Arguments

input	an input.
model_path	a path to the model.
keep	a vector of POS(s) to keep. Default is NULL.
format	a format of the output. Default is list.

Value

a list object.

Examples

```
data(sentence_example)
res_pos <- pos_simple(sentence_example$text)
```

sentence_example	<i>An example sentence</i>
------------------	----------------------------

Description

An example sentence

Usage

```
sentence_example
```

Format

A data.frame with a single row and a single column:

text a sentence in Japanese

Source

Aozora Bunko: <https://www.aozora.gr.jp/>

tokenize	<i>An R wrapper for Jagger's tokenizer</i>
----------	--

Description

An R wrapper for Jagger's tokenizer

Usage

```
tokenize(input, model_path = NULL, keep = NULL, concat = TRUE)
```

Arguments

input	an input.
model_path	a path to the model.
keep	a vector of POS(s) to keep. Default is NULL.
concat	logical. If TRUE, the function returns a concatenated string. Default is TRUE.

Value

a vector (if concat = TRUE) or a list (if concat = FALSE).

Examples

```
data(sentence_example)
res_tokenize <- tokenize(sentence_example$text)
```

tokenize_tbl*An R wrapper for Jagger's tokenizer (a tibble input)*

Description

An R wrapper for Jagger's tokenizer (a tibble input)

Usage

```
tokenize_tbl(tbl, column, model_path = NULL, keep = NULL)
```

Arguments

tbl	a tibble.
column	a column name of the tibble to tokenize.
model_path	a path to the model.
keep	a vector of POS(s) to keep. Default is NULL.

Value

a tibble.

Examples

```
data(sentence_example)
res_tokenize <- tokenize_tbl(tibble::as_tibble(sentence_example), "text")
```

Index

* **datasets**
 sentence_example, [5](#)

 lemmatize, [2](#)
 lemmatize_tbl, [3](#)

 pos, [3](#)
 pos_simple, [4](#)

 sentence_example, [5](#)

 tokenize, [5](#)
 tokenize_tbl, [6](#)